




**ECO**  
RADIATORS



## VENICE RANGE

EXTRUDED ALUMINIUM RADIATORS

Maximum operative pressure: 600kPa (6 Bar)

The thermal power complies with the European Standard UNI EN 442-2


Warranty: 15 years

Radiators are assembled from 2 to 10 elements

Standard colour RAL 9010

The first among the aluminum radiators to be devised and patented, VENICE wrote the story of this innovative technology, quickly becoming the symbol of Faral and a bestseller worldwide. To enact its great success were the characteristics of high thermal efficiency, lightweight and ease of installation. The fully recyclable material and the consequent substantial energy saving, through its use in systems with low operating temperatures, fueled by the most innovative energy sources, continue to make Tropical a modern product and in step with the times. After decades of success, MILAN presents itself to the public with a new design 100% Italian, softer and more appealing in order to continue to be the perfect for any style of decor

MODEL	A Distance Between the Centres (mm)	B Height (mm)	C Depth (mm)	D Width (mm)	Diameter (inch)	Water Content (litre per element)	Thermal Power EN 442 $\Delta t = 50K$ (watt per element)	Thermal Power EN 442 $\Delta t = 30K$ (watt per element)	Exponent (N)
VENICE	1000	1042	80	80	1"	0.43	174	87	1,351
VENICE	1200	1242	80	80	1"	0.49	200	100	1,351
VENICE	1400	1442	80	80	1"	0.55	224	113	1,350
VENICE	1600	1642	80	80	1"	0.62	248	124	1,350
VENICE	1800	1842	80	80	1"	0.68	271	136	1,350
VENICE	2000	2042	80	80	1"	0.75	293	147	1,349



**VENICE** was the first extruded aluminium radiator in the world and, like any self-respecting record, it was a model to imitate for many others. This only information may be enough to communicate this product's prestige and importance, but its success shall also be conferred to the ease of installation and the thermal performances!

